

## Claims

1. An injection unit which is moveable on runners (6) of the machine frame (7) of an injection molding machine with the aid of a running gear (40) and comprises a drive unit (10, 23) for axially displacing and pressing the plasticizing cylinder (2) to the injection mold,

characterized in that

the injection unit (1) is supported by a support (5) which is moveable on runners of the frame (7) of the injection molding machine and comprises an individual drive (10, 23) for pressing the plasticizing cylinder (2) to the injection mold (14) while achieving a centric sealing connection.

2. The injection unit according to Claim 1,

characterized in that

the support (5) is formed as a running gear (40) with an undercarriage (22) preferably comprising four guide shoes (8, 8').

3. The injection unit according to Claim 1 or 2,

characterized in that

the support (5) has two lateral support cheeks (44, 45), which provide the plasticizing cylinder (2) with articulated support via rotary pins (9).

4. The injection unit according to one of Claims 1 to 3,

characterized in that

the support (5) features a downward-facing fish joint (12) with a joint (11) for a drive axis (13).

5. The injection unit according to one of Claims 1 to 4,

characterized in that

the active axis of the fish joint connection (12) is disposed at the center of the machine (M-M) and in parallel to the axis of the plasticizing cylinder (2).

6. The injection unit according to Claim 5,  
characterized in that  
the active axis is preferably disposed at approximately the frame level, especially below the level of the runners (6).

7. The injection unit according to one of Claims 1 to 6,  
characterized in that  
the individual drive has an electric motor (10), in particular a servo motor, as well as a spindle overdrive (23).

8. The injection unit according to one of Claims 1 to 7,  
characterized in that  
the support (5) in the region between the upper rotary pins (9) and the lower joint (11) and the running gear (40) is rigidly formed, with deformation under stress being close to zero.

9. The injection unit according to one of Claims 1 to 8,  
characterized in that  
the guide shoes (8, 8') are designed as spherical rotary spindles, the horizontal spacing with respect to the tension-stressed guide shoes (8, 8') being greater than the corresponding spacing of the pressure-stressed guide shoes (8, 8'), to offset the K factor with regard to tension and pressure balancing.

10. The injection unit according to one of Claims 1 to 9,  
characterized in that  
the injection unit (1) includes a drive unit (4) for the rotational and axial movement of the plasticizing worm (3), said drive unit being supported by the support (5) as well as an additional guide shoe unit (15) on the frame (7), wherein the plasticizing cylinder (2) is firmly connected to the drive unit (4).

11. The injection unit according to one of Claims 1 to 10,  
characterized in that  
the additional guide shoe unit (15) has a lower drive bridge, on which the drive unit (4) is supported, said support being provided by a central support (25).

12. The injection unit according to Claim 11,  
characterized in that  
the additional guide shoe unit (15) has an adjustment device for both vertical and horizontal adjustment.

13. The injection unit according to one of Claims 1 to 12,  
characterized in that  
the support (5) and running gear (40) are disposed in the front section and the other guide shoe unit (15) in the rear section of the injection unit (1), the running gear (40) having four guide shoes and the guide shoe unit (8, 8') having two guide shoes.

14. The injection unit according to one of Claims 1 to 13,  
characterized in that  
the rotary pins (9) are at least approximately disposed in a shared horizontal plane with the axis of the plasticizing cylinder (2), in such a manner that during adjustment of the plasticizing cylinder tip (16) a pivoting movement can be completed in both a horizontal and a vertical plane.

15. Method for the adjustment of an injection unit (1), which is moveable on runners (6) of the machine frame of an injection molding machine with the aid of a running gear (40) and comprises a drive unit for axially displacing and pressing the plasticizing cylinder (2) to the injection mold (14),  
characterized in that  
when there is an insufficient concentric sealing connection, the plasticizing cylinder tip (16) is adjusted to the injection mold port (17) by means of a slight rotational movement of the entire injection molding unit (1) in both a vertical and horizontal plane prior to production.